

## Type of Cameras

### MCD 3300

1/3" 520 TVL Color Mini Dome Camera



#### Features

- Ultra Compact mini Color Dome
- Digital DSP 520TVL High-Resolution
- Advanced 1/3" CCD image sensor with Auto-CCD-Iris for indoor/outdoor applications
- Do not requires Auto Iris Lens for lighting control
- AES Auto Electronic Shutter
- Built-in Back-Light Compensation

### ED 350

1/3" 560 TVL Color Mini Dome Camera



#### Features

- 1/3" Sony Super HAD CCD image sensor with approximately 410,000 pixels
- 560 TVL of horizontal resolution
- Revolutionary integrated 10-bit Digital Signal Processor (DSP) delivers sharp color images and excellent picture quality
- Low light sensitivity 0.5 lux/F=1.2
- Wide-range automatic electronic shutter: up to 1/100,000
- Manual zoom lens with adjustable viewing range
- Pure Vision Technology

### EBD330I

1/3" 560 TVL Color Mini Dome Camera



#### Features

- Low light sensitivity 0.4 Lux/F=1.2 (AGC ON) is achieved by using the advanced 1/3" Super HAD CCD
- High Resolution 520TVL
- 3-Axis facilitates easy angle adjustment
- Individual lens glass to avoid remaining image from light reflection
- Lifespan of IR LED is 20,000 hours

## Type of Cameras

### EQ550

560 TVL Box Type Color Camera with True Day/Night



#### Features

- Advanced 16-bit Digital Signal Processor (DSP) delivers excellent picture quality and performance
- True Day/Night function with IR cut filter
- Built-in Dynamic Noise Reduction (DNR) for noise reduction and a 70% saving of disk storage
- Super low light with high sensitivity of 0.002 Lux/F=1.2
- OSD setting menu
- Support Motion Detection function and Privacy function
- Support either C-mount or CS-mount (optional), needs to have C/CS mount ring regardless

### ECZ330

520 TVL Weather Resistant Mini IR Bullet



#### Features

- 1/3" Sony Interline Transfer Super HAD CCD
- Low light sensitivity of 0.4 Lux/F=1.2
- 520 TVL of horizontal resolution
- Electronic shutter and AGC allows camera to be operated in environments with various light levels
- IR Wavelength 850nm
- Vari-frequency IR control
- 50°~78° viewing angle
- 10~15 meters / 33~59 feet of IR range
- Compact size for discreet surveillance
- Weather resistant IP66 rated

### EPTZ830

540TVL, Outdoor Speed Dome with Day/Night (22x Optical Zoom)



#### Features

- 1/4 SONY Super HAD CCD II with a Digital Slow Shutter (DSS) and Day/Night mode
- 540 TV lines; PAL/NTSC image formats support
- White balance function makes the shades of color more natural in different light conditions
- Auto and fast focus increases the searching speed and
- Auto iris adjusts the monitoring image to the best brightness
- Color / B&W images auto switching to enhance the sensitivity in a low light condition or at night
- Excellent position accuracy to  $\pm 0.1$  degree
- From super low [0.01°/sec] to high fast [360°/sec] pan/tilt
- Weather resistant IP66 rated

## EKB500

### Multi-Function Keyboard Controller



#### Features

- Capable of controlling speed dome cameras, DVRs and monitors
- Centralized control of up to 999 cameras from a single controller
- Password protected to prevent unauthorized users
- 3-D Joystick for PTZ control functions and Jog Shuttle for DVR control
- Two independent communication ports with selectable baud rate and protocol
- Customized, upgradeable firmware for specific applications
- Auto tracking by external signal processor unit
- Preset position and pattern control; full programmable preset tour

## ECOR264x1

### 16 Ch. H.264 DVR with GUI Menu, Built-in DVD Burner and 2 Internal HDDs



#### Features

- H.264 compression format for efficient disk utilization and network bandwidth conservation
- Real time recording and playback rate for all cameras
- Normal and event recording frame rate can be set independently for each camera
- Main monitor: VGA (800x600, 1280x1024) or BNC outputs
- Call monitor: additional composite BNC output with multiplex and/or sequenced views
- Simultaneous recording at D1 or 2CIF with real time streaming at CIF for remote web viewing to conserve bandwidth
- Pentaplex operation: simultaneous live, recording, playback, archiving and remote viewing
- Free EverFocus DDNS service - static IP address is not required for reliable remote access
- Remote configuration support from the built-in web interface
- Multiple Control Inputs: mouse, front panel, IR remote controller
- User friendly GUI menu with graphical icons & visual indicators



## Camera



### SCD-2010/2030

High Resolution Mini Dome Camera

- Built-in auto iris fixed lens
- SCD-2010 : 3mm
- SCD-2030 : 6mm



### SCD-2080

High Resolution Varifocal Dome Camera

- 600TV lines
- Built-in 3.6x (2.8 ~ 10mm) varifocal lens



### SID-450/452

1/3" High Resolution, Day & Night Dome Camera



### SCB-200

1/3" High Resolution Camera



### SCB-3001

Super High Resolution Camera

- High resolution 650TV lines
- Low light sensitivity of min. 0.3Lux



### SCP-2120

12x High Resolution PTZ Dome Camera

- 12x Optical Zoom
- 0.2Lux Ultra-Low Light Sensitivity



### SCP-3250/2250

25x High Resolution WDR PTZ Dome Camera

- SCP-3250 : WDR support



## Digital Recorder



**SRD-450**  
4CH H.264 Digital Video Recorder



**SRD-870/870D(C)**  
8CH H.264 Digital Video Recorder

- SRD-870D : Built-in DVD-RW
- SRD-870DC : Coaxial communication



**SRD-1652D/852D**  
16CH/8CH CIF Real-time H.264 Digital Video Recorder



**SVR-1645**  
16 Channel DVR



**SVR-3200**  
32 Channel Premium DVR with 960fps at half D1 resolution